

SIMATIC IFP1900 Flat Panel 19" display (16: 9), without touch, only display, Standard up to 5 m, 1366x 768 pixels, for 24 V DC, display port/DVI interface incl. DVI cable 1.8 m



Figure similar

General information	
Product type designation	IFP1900
Short designation	Flat Panel 19" display
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	18.5 in
Screen diagonal [cm]	47 cm
Display width	409.8 mm
Display height	230.4 mm
Viewing angle	170° x 160°
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Resolution (pixels)	
• Horizontal image resolution	1 366 Pixel
• Vertical image resolution	768 Pixel
• Pixel size, horizontal	0.3 mm
• Pixel size, vertical	0.3 mm

General features	
• Detachable from computer unit	5 m
• Brightness/contrast	300 cd/m ² / 1 000:1
• non-reflective and tempered mineral glass screen	Yes
• Luminance	300 cd/m ²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Keyboard fonts	
• Function keys	No
Installation type/mounting	
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss, typ.	40 W
Power loss, max.	65 W
Interfaces	
Video interfaces	
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	No
Degree and class of protection	
IP65 at front	Yes
Enclosure Type 4 at the front	Yes
NEMA4 at the front	No
NEMA4X at the front	No
IP20 rear	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes; Corresponds to UL 508

RCM (formerly C-TICK)	Yes
KC approval	Yes
Use in hazardous areas	
• FM Class I Division 2	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)

Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C

Relative humidity	
• Operation, max.	95 %; no condensation

Vibrations	
• Vibration load in operation	1 gn
• Vibration load during transport/storage	1 gn

Shock testing	
• Shock load during operation	15 gn
• Shock load during transport/storage	15 gn

Mechanics/material

Enclosure material (front)	
• Aluminum	Yes

Dimensions

Width of the housing front	483 mm
Height of housing front	337 mm
Mounting cutout, width	465 mm; Tolerance: +1 mm
Mounting cutout, height	319 mm; Tolerance: +1 mm
Overall depth	62.5 mm

Weights

Weight without packaging	5.5 kg
Weight incl. packaging	6.5 kg

last modified: 08/13/2018