

SIMATIC S7-1500, Front connector in push-in design, 40-pole, for 35 mm wide modules incl. 4 potential bridges and cable ties



Connection method

Connection I/O signals

- Connection method
- Number of lines per connection

Push-in terminal

1; or combination of 2 conductors of up to 1.5 mm² (total) in a shared ferrule

Conductor cross-section in mm²

— Connectable cable cross-sections for massive cables, min.

0.25 mm²

— Connectable cable cross-sections for massive cables, min.

1.5 mm²

— Connectable cable cross-sections for flexible cables without end sleeve, min.

0.25 mm²

— Connectable cable cross-sections for flexible cables without end sleeve, max.

1.5 mm²

— Connectable cable cross-sections for flexible cables with end sleeve, min.

0.25 mm²

— Connectable cable cross-sections for flexible cables with end sleeve, max.

1.5 mm²

Conductor cross-section acc. to AWG

- Connectable cable cross-sections for massive cables, min. 24
- Connectable cable cross-sections for massive cables, min. 16
- Connectable cable cross-sections for flexible cables without end sleeve, min. 24
- Connectable cable cross-sections for flexible cables without end sleeve, max. 16
- Connectable cable cross-sections for flexible cables with end sleeve, min. 24
- Connectable cable cross-sections for flexible cables with end sleeve, max. 16

24
16
24
16
24
16

Wire end processing

- Stripped length of cables, min. 8 mm
- Stripped length of cables, max. 11 mm
- End sleeve acc. to DIN 46228 without plastic sleeve Form A, 10 mm long
- End sleeve acc. to DIN 46228 with plastic sleeve Form E, 8 mm and 10 mm long

8 mm
11 mm
Form A, 10 mm long
Form E, 8 mm and 10 mm long

Mounting

- Tool

Screwdriver, conical design, 3 mm to 3.5 mm

Dimensions

Width	25.5 mm
Height	131 mm
Depth	37 mm

Weights

Weight, approx.	123 g
-----------------	-------

last modified: 08/16/2018