

SIMATIC S7-300, cam controller, FM 352, electronic incl. configuration package on CD



Figure similar

Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC 	Yes
Input current	
from load voltage L+ (without load), max.	200 mA
from backplane bus 5 V DC, max.	100 mA
Encoder supply	
5 V encoder supply	
<ul style="list-style-type: none"> • 5 V 	Yes
<ul style="list-style-type: none"> • Output current, max. 	300 mA
<ul style="list-style-type: none"> • Cable length, max. 	32 m
24 V encoder supply	
<ul style="list-style-type: none"> • 24 V 	Yes
<ul style="list-style-type: none"> • Output current, max. 	300 mA
<ul style="list-style-type: none"> • Cable length, max. 	100 m
Power loss	

Power loss, typ.	8.1 W
Digital inputs	
Number of digital inputs	4
Functions	Reference point switch, set floating actual value/length measurement, brake release, enable track output no. 3
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) for signal "0" for signal "1" 	24 V -30 to +5V +11 to +30V
Input current	
<ul style="list-style-type: none"> for signal "0", max. (permissible quiescent current) for signal "1", typ. 	2 mA 9 mA
Digital outputs	
Number of digital outputs	13
Functions	Cam track
Short-circuit protection	Yes
Output voltage	
<ul style="list-style-type: none"> Rated value (DC) for signal "1", min. 	24 V UP - 0.8 V
Output current	
<ul style="list-style-type: none"> for signal "1" permissible range for 0 to 60 °C, min. for signal "1" permissible range for 0 to 60 °C, max. for signal "0" residual current, max. 	5 mA; with UPmax 600 mA; with UPmax 0.5 mA
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> Incremental encoder (symmetrical) Incremental encoder (asymmetrical) Absolute encoder (SSI) 2-wire sensor <ul style="list-style-type: none"> permissible quiescent current (2-wire sensor), max. 	Yes Yes Yes Yes 2 mA
Encoder signals, incremental encoder (symmetrical)	
<ul style="list-style-type: none"> Trace mark signals Zero mark signal Input voltage Input frequency, max. 	A, notA, B, notB N, notN 5 V difference signal (phys. RS 422) 1 MHz
Encoder signals, incremental encoder (asymmetrical)	
<ul style="list-style-type: none"> Trace mark signals Zero mark signal 	A, B N

• Input voltage	24 V
• Input frequency, max.	50 kHz; 50 kHz for 25 m cable length; 25 kHz for 100 m cable length
Encoder signals, absolute encoder (SSI)	
• Data signal	DATA, notDATA
• Clock signal	CL, notCL
• Telegram length, parameterizable	13 or 25 bit
• Clock frequency, max.	1 MHz
• Gray code	Yes
• Cable length, shielded, max.	320 m; at max. 125 kHz
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	No
Potential separation digital outputs	
• Potential separation digital outputs	No
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Connection method	
required front connector	1x 20-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	550 g
last modified:	08/16/2018