

SIMATIC S7-300, Front connector for signal modules with spring-loaded contacts, 20-pole



General information

Product type designation	Front connector
--------------------------	-----------------

Ambient conditions

Ambient temperature during operation

- | | |
|--------|-------|
| • min. | 0 °C |
| • max. | 60 °C |

Ambient temperature during storage/transportation

- | | |
|--------|--------|
| • min. | -40 °C |
| • max. | 70 °C |

Accessories

belongs to product	S7-300
--------------------	--------

Connection method

Connection I/O signals

- | | |
|----------------------------------|--|
| • Connection method | Spring terminals |
| • Number of lines per connection | 1; or combination of 2 conductors of up to 1.5 mm ² (total) in a shared ferrule |

Conductor cross-section in mm ²
--

- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for flexible cables without end sleeve, min.
- Connectable cable cross-sections for flexible cables without end sleeve, max.
- Connectable cable cross-sections for flexible cables with end sleeve, min.
- Connectable cable cross-sections for flexible cables with end sleeve, max.

0.25 mm²
 1.5 mm²
 0.25 mm²
 1.5 mm²
 0.25 mm²
 1.5 mm²

Conductor cross-section acc. to AWG

- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for flexible cables without end sleeve, min.
- Connectable cable cross-sections for flexible cables without end sleeve, max.
- Connectable cable cross-sections for flexible cables with end sleeve, min.
- Connectable cable cross-sections for flexible cables with end sleeve, max.

24
 16
 24
 16
 24
 16

Wire end processing

- Stripped length of cables, min.
- Stripped length of cables, max.
- End sleeve acc. to DIN 46228 without plastic sleeve
- End sleeve acc. to DIN 46228 with plastic sleeve

6 mm
 6 mm
 Design A, 5 mm to 7 mm long
 Design E, up to 6 mm long

Dimensions

Width	23 mm
Height	131 mm
Depth	36 mm

Weights

Weight, approx.	61 g
-----------------	------

last modified: 08/16/2018