

SIMATIC PCS 7, PS 405 4A XTR S7-400 power supply Wide range, 24/48/60 V DC; 5 V DC/4 A, ATEX approbation identifier for extended temperature range and with conformal coating

General information

Product type designation	PS 405
--------------------------	--------

Supply voltage

Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC • 48 V DC • 60 V DC 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
permissible range, lower limit (DC)	19.2 V; Dynamic 18.5 V
permissible range, upper limit (DC)	72 V; dynamic 75.5 V

Mains buffering

<ul style="list-style-type: none"> • Mains/voltage failure stored energy time • Mains buffering according to NAMUR recommendation 	<p>20 ms</p> <p>Yes</p>
---	-------------------------

Input current

Rated value at 24 V DC	2 A
Rated value at 48 V DC	1 000 mA
Rated value at 60 V DC	800 mA
Inrush current, max.	18 A; Full width at half maximum 20 ms

Output voltage

Type of output voltage	DC
Rated value (DC)	
<ul style="list-style-type: none"> • 5 V DC • 24 V DC 	<p>Yes</p> <p>Yes</p>

Output current

for backplane bus (5 V DC), max.	4 A; no base load required
for backplane bus (24 V DC), max.	0.5 A; idling-proof
Short-circuit protection	Yes

Power

Active power input, typ.	48 W
--------------------------	------

Power loss

Power loss, typ.	16 W
------------------	------

Battery

Backup battery	
• Backup battery (optional)	Yes; 1x lithium AA; 3.6 V / 2.2 Ah
Hardware configuration	
Slots	
• required slots	1
Potential separation	
primary/secondary	Yes
Degree and class of protection	
Equipment protection class	I, with protective conductor
Standards, approvals, certificates	
FM approval	Yes; Ta: 0 °C to 70 °C T4
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	70 °C
Connection method	
Connecting cables/cross-sections	3x 1.5 mm ² , solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
Dimensions	
Width	25 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	800 g
last modified:	08/13/2018