HDC enclosures HDC IP68 16B TOS 2PG21



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMCresistant.

General ordering data

| HDC IP68 16B TOS 2PG21 | |
|---|--|
| <u>1082740000</u> | |
| HDC enclosures, Size: 6, Protection degree: IP68, IP69K, Plug housing, Screw plug, Standard, Size of cable entries: PG 21 | |
| 4032248845767 | |
| 1 pc(s). | |
| | |

HDC enclosures HDC IP68 16B TOS 2PG21

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

| Dimensions and weights | | | |
|---|------------------------------------|---|----------------------------------|
| Width | 58 mm | Width (inches) | 2.283 inch |
| Height | 110.5 mm | Height (inches) | 4.35 inch |
| Net weight | 604 g | | |
| Temperatures | | | |
| Limit temperature | -50 °C 125 °C | | |
| Dimensions | | | |
| | | | |
| Cable entry | w. threading | Height of housing B | 164 mm |
| Total length housing | 110.5 mm | | |
| General data | | | |
| ENACL . | | | P 4 1 1 1 1 |
| EMC housings Material of locking element | Yes Stainless steel, rust-proof | Housing main material Protection degree | diecast aluminium IP68, IP69K |
| Surface finish | Powder coating | Tightening torque | 6.5 Nm |
| Version | rowder country | | 0.0 1111 |
| version | | | |
| Cable entry | w. threading | Clamp version | Screw plug |
| Design | Standard | Design of housing | Plug housing |
| Design of locking system | Screw plug | Internal thread | PG 21 |
| Number of cable entry on top | 2 | Number of cable entry sideways | 0 |
| Size | 6 | Size of cable entries | PG 21 |
| Suitable for ModuPlug [®] | Yes | Tightening torque | 6.5 Nm |
| Top part/bottom part/lid | upper part | Туре | Plug |
| Classifications | | | |
| | | | |
| ETIM 6.0 | EC000437 | eClass 6.2 | 27-14-34-19 |
| eClass 7.1 eClass 9.0 | 27-44-05-15 27-44-05-15 | eClass 8.1 eClass 9.1 | 27-44-05-15 27-44-02-02 |
| | 27-44-05-15 | eciass 9.1 | 27-44-02-02 |
| Approvals | | | |
| Approvals | | | |
| ROHS | Conform | | |
| Downloads | | | |
| Brochure/Catalogue | CAT 3 HDC 17/18 EN | | |
| | FL FIELDWIRING EN | | |
| Engineering Data | <u>EPLAN</u> | | |